

RC90c2



Specifications:

Channels	no	2
Class	Type	AB
Power @14,4V /1.0% THD		
@ 4 ohm stereo:	Wrms	2X 85
@ 2 ohm stereo:	Wrms	2X 130
@ 4 ohm mono:	Wrms	1X 260
Operation supply	V	10-16
Thermal protection	°C	80
THD @ 4 Ω / 50% Pmax	%	0.5
Signal/noise	dB	100
Band width +- 1 dB	Hz	20-20000
Input sensitivity	Vrms	0.2-10
Low input impedance	Ω	17k
High input impedance	Ω	50(with RC-HLT)
Damping @ 80 Hz		50
Power consumption, idle	A	0.5
Power cons. 4 Ω stereo	A	18
Power cons. 4 Ω bridged	A	32
Power cons. 2 Ω stereo	A	32
Weight	kg	1.67
Dimensions	l/w/h	215/150/50mm

Features:

- Input with low- or high-level signal
- Stable at 2ohm stereo per channel and 4 ohm bridge mode
- High-level with autosense function (no remote signal required)
- Variable switchable Low Pass Filter from 45 to 225 Hz
- Variable switchable High Pass Filter from 45 to 225 Hz

Miscellaneous:

- Protection for overheating, overloading, short circuitry and speaker DC protection
- Massive heavy aluminum-heat sink